









## **TECHNICAL SPECIFICATIONS**

		Units	DD 90		
		WEIGHTS			
Maximum Operating Weight		Kg	9300		
Operating Weight		Kg	9000		
Weight On Front Drum		Kg	4500		
Weight On Rear Drum		Kg	4500		
Static Linear Load-Front		Kg/Cm	26.8		
Static Linear Load-Rear		Kg/Cm	26.8		
DIMENSIONS					
А	Wheel Base		2900 mm		
В	Overall Width		1922 mm		
С	Axle to Rear Face		820 mm		
D1 = D2	Drum Diameter		1200 mm		
H1	Total Travel Clearand	e with Canopy	3125 mm		
К	Ground Clearance		310 mm		
L	Total Travel Length		4550 mm		
S	Drum Thickness		17 mm		
W1 = W2	Drum Width		1680 mm		
E1	Front Departure Ang	le	32°		
E2	Rear Departure Angl	e	32°		
ENGINE					
Make			ESCORTS E4.286 TCI		
Specification			4 Cylinder, Water Cooled,		
			Bharat Stage III Power 74HP		
			@ 2300 rpm		
Electrical System			12V		
VIBRATION SYSTEM					
Frequency		Hz	33/50		
High Amplitude		mm	1.0		
Low Amplitude		mm	0.4		
SPEED					
Travelling Speed		Km/hr	0-9.5		

	Units	DD 90			
GRADEABILITY					
Gradeability Without Vibration	%	45			
Gradeability With Vibration	%	30			
STEERING (Hydrostatic Power Steering)					
Steering Angle		±30°			
Oscillation Angle		±10°			
BRAKES					
Service Brake Parking Brake Emergency Stop		Hydrostatic Spring Loaded Brake, Hydraulically Released on both drums Spring Loaded Brake, Hydraulically Released on both drums			
Fuel Tank Capacity	Lts Lts	140			
Hydraulic Oil Tank Capacity	Lts	700			
Water Tank Capacity	LIS	700			
SPRINKLER SYSTEM					
4 stage filtration pressure sprinkle, Foot Actuation (Manual), Interval (Automatic), Corrosion free plastic water tank on each drum.					
SAFETY FEATURES					
Neutral Start Switch, Air Filter Clog Indicator, Hydraulic Filter Clog Indicator, Reverse buzzer, Auto-Vibration & Sprinkle Cut off. Audio Visual alarm during high coolant temperature and low pressure to be added.					
STANDARD EQUIPMENT					
Swinging operator seat for better	Swinging operator seat for better drum visibility, Tiltable Steering, Larger operator				

Swinging operator seat for better drum visibility, Tiltable Steering, Larger operator platform accessible from each side, Electric operator controls, FRP roof, Instrument Panel With a range of control instruments including hour meter & Light Equipment.

## **OPTIONAL FITMENT**

Switchable to single/either Drum Vibration, Cabin, Heater, Demister, Edge Cutting and pressing Discs, Cold Start Kit.

**Channel Partner** 

The information contained in this leaflet is intended to be of general nature only. We reserve the right to change the specifications without any prior notice. All dimensions and weights are variable with in ±2.5%